



**C 400H**  
**C 400H x4**  
**C 500H**  
**C 500H x4**



[www.ausa.com](http://www.ausa.com)



FEM-AEM

**AUSA Center, S.L.U.** ● Ctra. de Vic, Km 2.8 - P.O.B. 194, 08243 Manresa - BARCELONA (ESPAÑA) Tel.: +34 93 874 73 11 E-mail: [ausa@ausa.com](mailto:ausa@ausa.com)



**AUSA Madrid** ● Pol. Ind. Coslada-Marconi 15-17, 28823 Coslada - MADRID (ESPAÑA) Tel.: +34 91 669 00 06 E-mail: [ausa.madrid@ausa.com](mailto:ausa.madrid@ausa.com)  
**AUSA France** ● Z. I. Saint Charles-Rue de Zürich, 66000 PERPIGNAN (FRANCE) Tel.: +33 (0) 4 68 54 38 97 E-mail: [ausa.france@ausa.com](mailto:ausa.france@ausa.com)  
**AUSA** ● Unit 16 Hollows Works - Shawclough Road - Rochdale - Lancs OL12 6LN (U.K.) Tel.: +44 (0) 1706 64 96 91 E-mail: [ausa.uk@ausa.com](mailto:ausa.uk@ausa.com)  
**AUSA Repräsentanzbüro Deutschland** ● Heinrich - Welken Str. 5, 59069 HAMM - RHYNERN (GERMANY) Tel.: +49 2385922245 E-mail: [ausa.deutschland@ausa.com](mailto:ausa.deutschland@ausa.com)  
**AUSA Northamerica Corp.** ● 2655 Le Jeune Road - Suite 808, CORAL GABLES FL 33134 (USA) Toll free: 1 800 820 AUSA E-mail: [ausa.corp@ausa.com](mailto:ausa.corp@ausa.com)


**BEIJING Rep. Office** ● Address Room 527, HengXiang Building, Tuanjiehu Nanli, Chaoyang District. - Beijing 100026 CHINA  
 Tel: 86-10-8597 1983 - Fax: 86-10-8597 1993 - E-mail: [ausa.china@ausa.com](mailto:ausa.china@ausa.com)

(Sede central AUSA-Manresa)

**C 400H\_4000 Kg**  
**C 500H\_5000 Kg**



DIMENSIONS (mm)	C 400 H	C 400 H x4	C 500 H	C 500 Hx4
A	2335	2335	2335	2335
B	280	280	280	280
C	300	300	300	300
D	1640	1700	1640	1700
E	2000	2000	2000	2000
F	3560	4770	3560	4770
G	3050	3205	3050	3205
I	120	120	130	130
J	50	50	60	60
K	718	718	728	728
L	4568	4568	4623	4623
M	660	600	705	645
N	1990	2050	1990	2050
O	1200	1200	1200	1200
P	5680	6820	5680	6820



Type of mast	Maximum lifting height (mm)	Free lift (mm)
Duplex (Std.)	3700	100
Duplex	4500	100
Triplex (free lift)	4250	1393
Triplex (free lift)	5450	1793
Triplex (free lift)	6800	2243

H Machine height with mast retracted (mm)				Machine height with mast extended (mm)				Load (Kg) at max. height			
C 400 H	C 500 H	C400Hx4	C500Hx4	C 400H	C500H	C400Hx4	C500Hx4	C 400H	C500H	C400Hx4	C500Hx4
2750	2750	2750	2750	4585	4585	4585	4585	4000	5000	4000	5000
3150	3150	3150	3150	5385	5385	5385	5385	4000	4900	4000	4900
2350	2350	2350	2350	5262	5262	5262	5262	4000	5000	4000	5000
2750	2750	2750	2750	6462	6462	6462	6462	1200	1250	1200	1250
3200	3200	3200	3200	7812	7812	7812	7812	450	600	450	600

### TECHNICAL SPECIFICATIONS

	C 400H	C 400H x4	C 500H	C 500H x4
<b>Load capacity (Kg)</b>	4000		5000	
<b>Centre of gravity (mm)</b>	500		600	
<b>Lifting height (Standard duplex mast) (mm)</b>	3700			
<b>Engine</b>	Turbodiesel			
Power acc./DIN 6270 B (KW/HP)	KUBOTA V3300T			
Power acc./DIN 70020 (KW/HP)	63 / 86 (2600 rpm)			
N° of cylinders	69 / 93 (2600 rpm)			
Cubic capacity (cc)	4			
Cooling system	3300			
<b>Traction</b>	2	4	2	4
<b>Transmission</b>	Hydrostatic with variable flow pump and automatic regulation Electric gear inverter Inching pedal			
<b>Unladen weight (Kg) (with full tanks)</b>	6700	6800	7500	7600
<b>Gradient negotiable (with full load)</b>	35%		30%	
<b>Speed (Maximum) (Km/h)</b>	20			
<b>Engine starting system</b>	Electric			
<b>Tyres</b>	Front 18 - 19,5 TL 16 PR	18 - 19,5 TL 16 PR	18 - 19,5 TL 16 PR	18 - 19,5 TL 16 PR
	Rear 8.15 - 15	10.0 / 75 - 15.3	8.15 - 15	10.0 / 75 - 15.3
<b>Steering</b>	Hydraulic. Working pressure 150 bar	Hydraulic. Working pressure 170 bar	Hydraulic. Working pressure 150 bar	Hydraulic. Working pressure 170 bar
<b>External turning circle (mm)</b>	3560	4770	3560	4770
<b>Tank capacity (l)</b>	Fuel 120	95	120	95
	Hydraulic fluid			
<b>Service brake</b>	Oil-immersed, multidisc, hydraulically driven			
<b>Parking brake</b>	Oil-immersed, multidisc, hydraulically driven			
<b>Hydraulic circuit</b>	30 - 10.6 cc. double gear pump			
<b>Operating pressures for accessories (bar)</b>	220 +5		230 +5	
<b>Forkcarriage</b>	FEM 3 - Width: 1660 mm		FEM 4 - Width: 1660 mm	

### STANDARD EQUIPMENT

Open cabin  
Ergonomic seat  
Seat belt  
Joystick  
Rotating beacon  
Side-shift  
Audible reverse warning

### OPTIONAL EQUIPMENT

Semi-closed cabin  
Full cabin with heater  
Front and rear lights  
4th hydraulic valve for accessories  
Catalytic converter  
Spark arrestor  
800, 1000 and 1500 litre hydraulic buckets  
Load Guard  
Radio